

# ***PRODUCT SUMMARY SHEET***

## **LEAD SUBSTITUTE**

**Mixes with unleaded fuels to make a fuel alternative or substitute to “Super” and or “LRP” (lead replacement petrol), for engines, which require leaded fuels. Provides the protection of high leaded fuel and will not damage catalytic converters.**

Product functions by depositing a sodium oxide coating on the valves which prevents metal contact, just as lead oxides coated the valves. Engines designed for leaded fuel and running with inadequate levels of lead can fail in as little as 60 hours.

Designed for: Motors requiring leaded fuels incl: Cars, Trucks, Farm Equipment, Outboards, Also race engines which suffer from excessive valve seat wear and piston scuffing when operated on low-lead or unleaded fuels.

Application: One bottle 12 oz treats 454 litres of unleaded or premium unleaded fuel used in regular driving. Big engines or engines working harder, towing etc, need to increase dosage accordingly. For fuel system cleanup, use 1 bottle Red Line SI-1 cleaner (See also Section 5.27) in full tank of fuel. SI-1 is compatible with Red Line Lead Substitute so add the required dose of Red Line Lead Substitute as per usual.

<b>Unleaded fuel Litres</b>	<b>Normal use Minimum dose ml</b>	<b>Unleaded fuel Litres</b>	<b>Normal use Minimum Dose ml</b>
5	4	75	59
10	8	80	63
15	12	85	66
20	16	90	70
25	20	95	74
30	23	100	78
35	27	150	117
40	31	200	156
45	35	250	195
50	39	300	235
55	43	350	274
60	47	400	313
65	51	450	352
70	55	454	355

### Available As

<b>BAR CODE</b>	<b>CODE</b>	<b>ITEM</b>	<b>UNIT SIZE</b>	<b>UNIT SIZE METRIC</b>
83522 60202	RL169	LEAD SUBSTITUTE	12FLOZ	355ml